

INSTALLATION INSTRUCTIONS

Counter Express DVDC0073

Tools and Materials that may be required:

- Adjustable wrench ½ or socket set
- 3/8 Inch drill bit/electric drill [concrete drill bit may be necessary for floor anchoring]
- Other tools/materials may also be necessary depending upon actual installation
- Installation Hardware Kit included – locate white hardware kit box

Installation Procedure:

Confirm installation site with onsite management prior to installation.

1. Remove unit from box and set on counter in desired position.

See Step 2 to secure the unit to the counter.

Skip to Step 6 to secure the unit to the wall.

2. Locate the keys, unlock and open the key-locked access door and remove false bottom.
3. Locate anchoring holes and center mark holes for drilling.

WARNING: DO NOT DRILL HOLES DIRECTLY ABOVE OR BELOW WALL OUTLETS

4. Remove unit and set aside to gain access to drill marks and drill holes. Note: 4 lag screws are also provided for possible solid counter and/or hollow anchoring configurations [see Figure 2].
5. Set collection unit on counter and align with holes. Locate 4 rounded head bolts with flat/locking washers and nuts (4, 3/8" X 1" - Supplied). Install bolts from bottom up (if properly installed, only the top of the round head bolts may be visible from the underside of the counter). Open access door of collection unit and install washers and nuts on rounded head bolts and tighten as needed. Reinstall false bottom, close and lock access door.
6. Position collection unit against the wall where unit is to be installed. Locate anchoring holes and center mark holes for drilling.

WARNING: DO NOT DRILL HOLES DIRECTLY ABOVE OR BELOW WALL OUTLETS

7. Remove unit and set aside to gain access to drill marks and drill holes. Note: 4 lag screws are also provided for possible solid wall or wall stud anchoring configurations [see Figure 2]

Wall Anchoring – re-position unit near install site wall and insert 4 toggle bolts through hole and spacers provided [see Figure 1 & 2]

8. Align unit against wall anchoring holes. Insert toggle bolt wing nut through wall anchoring holes and tighten as needed

dVault Company, Inc. • 9800 Mount Pyramid Court • Suite 400 • Englewood, Colorado • 80112
Phone: (720) 895-1908 • Fax: (720) 895-1909 • World Wide Web: <http://www.dvault.com>

The logo for dVault, featuring the word "dVault" in a bold, sans-serif font. The "d" is lowercase and the "Vault" is uppercase. The logo is positioned at the bottom right of the page, above a horizontal line.